



product data sheet

# ViscoDos-4000

## description



The dosing control ViscoDos-4000 is used to control volumetric dispenser with servo drive ViscoPro.

- easy integration in existing systems
- volumetric dosing
- adjustable flow rate
- automatic reverse flow
- 1 and more component systems possible
- control by BUS-systems (CAN-Bus, Profi-Bus)
- max. flexibility with included multifunctional interface converter
- analog and binary control inputs
- menu guided calibrating function
- fault and warning message in plain text
- language change german/english (others on demand)
- 9 parameter rates with 99 recipes
- easy update with USB stick
- robust keyboard (suitable for industrial usage)
- graphic display
- optimized for complete ViscoPro series

## application

- control of volumetric dispenser
- control of feed pumps in systems
- control of supply pressure to dosing system
- control of filling pumps
- control of more component systems

## technical data

electrical data (power supply)	230 V, 10 A, 50 Hz
housing (wxdxh)	380x380x210 mm
protection class	IP 54

## item no.

ViscoDos-4000	137517
Profi-Bus module	137706



## item information

### operating types

- quantity dosing (defined quantity is dispensed)
- recipe and parameter management
- high-low mode (one signal for start and stop, e.g. pressure control)
- dynamic dosing (adjustment to track speed)

### display

- display with direct input options as follows:
  - dosing quantity in ml
  - dosing speed in ml/s
  - calibration of pump size (ml/turn)
  - quantity of reverse flo in ml
  - speed of reverse flow
  - equalization quantity in ml
  - equalization speed
  - adjustable acceleration/declaration
- start button
- stop button
- failure message in plain text
- easy recipe and parameter management

### inputs

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• start (NO contact)</li> <li>• stop (NC contact)</li> <li>• external release (potential free)</li> <li>• speed adjustment (0-10 V)</li> <li>• 2x fill level (empty + nearly empty)</li> </ul> | <ul style="list-style-type: none"> <li>• supply pressure</li> <li>• dosing pressure</li> <li>• 4x 24 V power supply for sensors</li> </ul> |
|---|--|

### outputs

- ready (warning + fault)
- finished message
- optional: additional outputs

### additional types

- ViscoDos-4000 g (for ViscoPro-Cg)
- ViscoDos-4000 fu (for polyphase drives)
- ViscoDos-4000 2K

### scope of delivery

- dosing control ViscoDos-4000
- operation manual

### necessary and optional components

- dispensers required for dosing with ViscoPro drive (see separate data sheet)
- optional: bus module
- external control elements